



# DirectTex® Artist Backlite

Fields of application

**.02 .04 .05 .07**

## Specifications

-  **REF.** 564252 083
-  100 % polyester  
weave fabrics  
PVC-free, recyclable
-  ca. 155/ 252/ 310/ 505 cm  
ca. 61/ 99/ 122/ 199 inch  
other widths available on request
-  B-s1, d0    DIN EN 13501-1
-  ca. 250 g/m<sup>2</sup>  
ca. 7.4 oz/yd<sup>2</sup>
-  ca. 0.4 mm  
ca. 400 µm
-  rolls  
50/ 100 m  
55/ 109 yd
-  blank:    6-7  
DIN EN ISO 105-B02
-  **Light**  
blank:    31.9 %  
DIN EN 410
-  **UV**  
blank:    0.1 %  
DIN EN 410
-  blank:    95.03  
DIN 5033-1
-  ultrasonic cut
-  direct light

## Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside	•		•

## Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	1,4 %	1,8 %	•
190°C	1,5 %	2,7 %	
200°C	3,0 %	3,3 %	
210°C	3,5 %	4,2 %	

## Certifications



## DirectTex® Artist Backlite

Fields of application

**.02 .04 .05 .07**



Ref.-Nr.: 564252 083 | Preview print sample