

# DirectTex® Softimage 240®

Fields of application

**.02 .04 .05 .07**

## Specifications



599250 129



100 % polyester  
knit fabrics  
PVC-free, recyclable



ca. 160/ 252/ 320/ 505 cm  
ca. 63/ 99/ 126/ 199 inch  
other widths available on request



B-s1, d0    DIN EN 13501-1  
M1            NF P 92 503 - 507



ca. 240 g/m<sup>2</sup>  
ca. 7.08 oz/yd<sup>2</sup>



ca. 0.49 mm  
ca. 490 µm



rolls  
50/ 100 m  
55/ 109 yd



length: 644.5 N  
cross: 1223.9 N  
DIN EN ISO 13934-1



length: 61.8 %  
cross: 57.4 %  
DIN EN ISO 13934-1



length: 1.6 %  
cross: 0.9 %  
DIN EN 14704-1



cold, ultrasonic cut

## Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

## Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,5 %	1,2 %	
190°C	/ %	/ %	
200°C	/ %	/ %	•
210°C	0,5 %	2,5 %	

## Certifications



## DirectTex® Softimage 240

Fields of application

**.02 .04 .05 .07**



Ref.-Nr.: 599250 129 | Preview print sample