

# DirectTex® Backlite Premium

Fields of application

**.02 .04 .05 .07**

## Specifications



599280 139



100 % polyester  
knit fabrics  
PVC-free, recyclable



ca. 252/ 505 cm  
ca. 99/ 199 inch  
other widths available on request



B-s1, d0    DIN EN 13501-1  
Class A    ASTM E48-16  
NFPA 701    California Title 19



ca. 260 g/m<sup>2</sup>  
ca. 7.7 oz/yd<sup>2</sup>



ca. 0.5 mm  
ca. 500 µm



rolls  
50 m  
55 yd



blank: 15.1 %  
DIN EN 410



blank: 6  
DIN EN ISO 105-B02



cold, ultrasonic cut



direct light

## Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

## Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,4 %	0,7 %	•
190°C	0,6 %	1,2 %	
200°C	0,8 %	1,4 %	
210°C	1,3 %	2,0 %	

## Certifications





## DirectTex® Backlite Premium

Fields of application

**.02 .04 .05 .07**



Ref.-Nr.: 599280 139 | Preview print sample



**PONGS Technical Textiles GmbH**  
Bahnhofstraße 21 Phone +49 36645 350-0  
07919 Pausa-Mühltrorf salestt@pongs.de  
Germany www.pongs.com

Find the latest version by scanning the QR code.  
We reserve the right for technical modifications.  
The above mentioned details are non-binding.  
A tolerance of  $\pm 5\%$  is valid. Effective: 2021/01