

DirectTex® Illuminati

Fields of application

.02 .04 .05 .07

Specifications



599292 139



100 % polyester
knit fabrics
PVC-free, recyclable



ca. 160/ 252/ 320 cm
ca. 63/ 99/ 126 inch
other widths available on request



B-s1, d0 DIN EN 13501-1
M1 NF P 92 503 - 507



ca. 310 g/m²
ca. 9.1 oz/yd²



ca. 0.67 mm
ca. 670 µm



rolls
50 m
55 yd



blank: 5-6
DIN EN ISO 105-B02



length: 1.7 %
cross: 1.8 %
DIN EN 14704-1



indirect, direct light



cold, ultrasonic cut



length: 365.7 N
cross: 2055.1 N
DIN EN ISO 13934-1



length: 62.0 %
cross: 48.8 %
DIN EN ISO 13934-1



warp: 126.0 N
weft: 271.4 N
DIN EN ISO 9073-4

Printing methods

print	UV	Latex	Dyesub
Inside			•
Outside			

Article shrinkage

(50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,2 %	0,7 %	
190°C	0,2 %	0,9 %	•
200°C	0,4 %	1,1 %	
210°C	0,4 %	1,4 %	

Certifications



DirectTex® Illuminati

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 599292 139 | Preview print sample