

















PrintTex® Artist Mambo®

Fields of application

.02 .04 .05 .07

Specifications


-  **REF.** 564160 237
-  100 % polyester
weave fabrics
PVC-free, recyclable
-  ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request
-  B-s1, d0 DIN EN 13501-1
NFPA 701
-  ca. 170 g/m²
ca. 5.0 oz/yd²
-  ca. 0.30 mm
ca. 300 µm
-  rolls
50/ 100 m
55/ 109 yd
-  **Light**
blank: 28.1 %
DIN EN 410
-  **UV**
blank: 3.9 %
DIN EN 410
-  coated side: 7-8
uncoated side: 6
DIN EN ISO 105-B02
-  blank: 96.35
DIN 5033-1
-  indirect, direct light
-  cold, ultrasonic cut

-  warp: 1317 N
weft: 1353 N
DIN EN ISO 13934-1
-  warp: 31.3 %
weft: 31.6 %
DIN EN ISO 13934-1
-  warp: 0.8 %
weft: 1.2 %
DIN EN 14704-1

Printing methods

print	UV	Latex	Dyesub
Inside	•	•	
Outside			•

Certifications



PrintTex® Artist Mambo

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 564160 237 | Preview print sample